



LOW GLARE LED PANEL LIGHT

2 COLOUR OPTIONS AVAILABLE
(4000K / 6000K)



DRIVER BY
PHILIPS

- Low glare UGR < 19 in compliance with EN12464-1
- Philips driver (5 year warranty)
- Replacement for 600x600 Modular Fittings
- Save up to 60% on energy costs
- Instant start
- Flicker free
- Certified fire resistant
- Average life 50,000 hours
- Emergency lighting version available
- Dimmable version available
- Surface mounting kit available

 **50,000 Hrs**
Average Life

APPLICATIONS



Emergency
pack
available

SPECIFICATIONS

Item	833716	833723
Description	LED Panel, 596x596x11 48w 4000K White Frame	LED Panel, 596x596x11 48w 6000K White Frame
Colour Rendition (CRI)	Ra80	Ra80
CCT Range	3700 - 4200K	5700 - 6100K
Luminous Flux	3600 lm	3700 lm
Beam Angle	103°	103°
Driver Manufacturer	Philips	Philips
Warm Up Time	Instant	Instant
Power Input (50-60Hz AC)	48w, 220-240VAC, 50-60Hz	48w, 220-240VAC, 50-60Hz
Power Factor, Current	0.92, 1150mA	0.92, 1150mA
Lamp Type	2835 SMD	2835 SMD
Working Temperature	-20 ~ +40°C	-20 ~ +40°C
Construction	PC/AL/Steel	PC/AL/Steel
IP Rating	IP20	IP20
Certification	CE, RoHS	CE, RoHS
Energy Efficiency Label	A	A
Energy Consumption (Ec)	48 kWh / 1000 hrs	48 kWh / 1000 hrs
Lifetime	50,000 hours	50,000 hours
Warranty and LMF at EoL	5 Years, 70%	5 Years, 70%
Switching Cycles	100,000	100,000



Height	E-Max	Diameter
1.5 Meter	624 Lx	377 cm
2.0 Meter	351 Lx	503 cm
4.0 Meter	88 Lx	1006 cm
4.5 Meter	69 Lx	1131 cm
6.0 Meter	39 Lx	1508 cm

Beam Angle 103°

