



LED PANEL LIGHT

LOW GLARE LED PANEL - UGR<19



- Replacement for 600x600 Modular Fittings
- Low glare UGR <19 in compliance with EN12464-1
- Save up to 60% on energy costs
- Instant start. Flicker free
- No mercury or other hazardous materials
- 3 year warranty
- Emergency lighting version available
- Dimmable version available
- Surface mounting kit available



APPLICATIONS



Offices



Retail



Education



Commercial
Kitchens



Emergency
pack
available

LED PANEL LIGHT

LOW GLARE LED PANEL - UGR<19

Item	833420	835697	835703
Luminescence			
Description	LED panel 3000k	LED panel 4000k	LED panel 6000k
Luminous flux	3600lm	3600lm	3600lm
CCT range	2900 - 3100K	3850 - 4150K	5700 - 6300K
CRI	Ra80,5 SDCM	Ra80,5 SDCM	Ra80,5 SDCM
Beam angle	120°	120°	120°
Accent Lighting	No	No	No
Warm up time	Instant	Instant	Instant
Dimmable	Dimmable option available	Dimmable option available	Dimmable option available
Technical			
Power input (50-60Hz AC)	40W 240V AC	40W 240V AC	40W 240V AC
Power factor, current	0.9, 1000MA	0.9, 1000MA	0.9, 1000MA
Lamp type	LED	LED	LED
Fire rated	No	No	No
Working temperature	-20 ~ 45°C	-20 ~ 45°C	-20 ~ 45°C
Construction	Aluminium, PC	Aluminium, PC	Aluminium, PC
IP rating (Fascia)	IP40	IP40	IP40
Frame Finish	White frame	White frame	White frame
Dimensions	595x595x9	595x595x9	595x595x9
Efficiency			
Certification	CE, RoHS	CE, RoHS	CE, RoHS
Energy Efficiency Label	A+	A+	A+
Ec (Energy consumption)	40kWh/1000h	40kWh/1000h	40kWh/1000h
Lifetime	30,000 hours	30,000 hours	30,000 hours
Warranty & LMF at EoL	3 years, 50%	3 years, 50%	3 years, 50%
Switching cycles	50,000	50,000	50,000

Emergency Pack (to be ordered separately)

Emergency pack **Item: EM3**

